

Water Heaters

Wide Range of High Capacity Water Heaters

Water heaters designed for the marine environment in a range of capacities and material finishes

Available in The Americas only



Robust
- Marine grade materials
White epoxy coated, Stainless Steel or Marine Galvanised Steel

Multiple Options
- Range of capacities and heat exchanger options

Safety First
- Fixed temperature and pressure monitor for peace of mind

S300EW



White Epoxy Coated
Horizontal with Side Heat Exchanger Model



White Epoxy Coated
Horizontal Electric Only Model



Marine Galvanised Steel
Horizontal Rear Heat Exchanger Model



Stainless Steel
Front Heat Exchanger Model

Product Information

Model Specifications

Model	Capacity	Orientation	Heat Exchanger	PSI Rating	Overall Dimensions	Exterior Material	Weights (lbs)	
120 V	240 V	US Gals			inches (W,D,H)			
S300W		11 lts (3 gal)	Horizontal	Side	100 psi	14.5" x 14" x 13"	White Epoxy	14
S300EW	S350EW	11 lts (3 gal)	Horizontal	Electric	100 psi	14.5" x 14" x 13"	White Epoxy	14
F600	F650	23 lts (6 gal)	Horizontal	Front	100 psi	13" x 19" x 13"	Marine Galvanised Steel	26
F600W	F650W	23 lts (6 gal)	Horizontal	Front	100 psi	13" x 19" x 13"	White Epoxy	26
	F650WSR	23 lts (6 gal)	Horizontal	Front	75 psi	13" x 19" x 13"	White Epoxy	26
F700	F750	23 lts (6 gal)	Horizontal	Front	100 psi	13" x 19" x 13"	Stainless Steel	24
S600	S650	23 lts (6 gal)	Horizontal	Rear	100 psi	13" x 19" x 13"	Marine Galvanised Steel	26
S600W	S650W	23 lts (6 gal)	Horizontal	Rear	100 psi	13" x 19" x 13"	White Epoxy	26
S600EW		23 lts (6 gal)	Horizontal	Electric	100 psi	13" x 19" x 13"	White Epoxy	26
	S650E	23 lts (6 gal)	Horizontal	Electric	100 psi	13" x 19" x 13"	Marine Galvanised Steel	26
	S650EW-3000	23 lts (6 gal)	Horizontal	Electric	100 psi	13" x 19" x 13"	White Epoxy	26
S700	S750	23 lts (6 gal)	Horizontal	Rear	100 psi	13" x 19" x 13"	Stainless Steel	24
S700E	S750E	23 lts (6 gal)	Horizontal	Electric	100 psi	13" x 19" x 13"	Stainless Steel	24

Note: All Whale Water Heaters must be installed and serviced by a qualified electrician in accordance with the Whale appliance installation and operating instructions and appropriate electrical regulations and certifications.

Combination Electric/Heat Exchanger Or Electric Only Models

- Capacities available 3,6,11,20 and 28 US Gals
- Robust manufacturing
 - Hold down brackets welded to inner tank
- Double wall heat exchangers
 - Prevents accidental contamination of freshwater supply
- Safety controls
 - Integrated pressure relief valve and temperature monitor
- Sturdy, robust exteriors
 - Produced from marine grade stainless steel or epoxy coated
- Ignition protected
- Available in The Americas only

2 Year Warranty

Model Specifications

Model		Orientation	Heat Exchanger	Capacity (US Gals)	PSI Rating	Overall Dimensions inches (W,D,H)	Exterior Material	Shipping Weight (lbs)
120 V	240 V							
F1100	F1150	Horizontal	Front	11	100 psi	16"x 22" x 16"	Marine Galvanized Steel	34
F1100W	F1150W	Horizontal	Front	11	100 psi	16"x 22" x 16"	White Epoxy	34
	F1150WSR	Horizontal	Front	11	75 psi	16"x 22" x 16"	White Epoxy	34
F1200	F1250	Horizontal	Front	11	100 psi	16"x 22" x 16"	Stainless Steel	32
S1100	S1150	Horizontal	Rear	11	100 psi	16"x 22" x 16"	Marine Galvanized Steel	34
S1200	S1250	Horizontal	Rear	11	100 psi	16"x 22" x 16"	Stainless Steel	32
	H2050	Horizontal	Rear	20	100 psi	16"x 32" x 16"	Marine Galvanized Steel	48
	H2050EW	Horizontal	Electric	20	100 psi	16"x 32" x 16"	White Epoxy	48
	H2050EW-3000	Horizontal	Electric	20	100 psi	16"x 32" x 16"	White Epoxy	48
	H2050EW-4500	Horizontal	Electric	20	100 psi	16"x 32" x 16"	White Epoxy	48
H2200		Horizontal	Rear	20	100 psi	16" x 32" x 16"	Stainless Steel	47
	H2250E	Horizontal	Electric	20	100 psi	16" x 32" x 16"	Stainless Steel	47
HF2000	HF2050	Horizontal	Front	20	100 psi	16" x 32" x 16"	Marine Galvanized Steel	48
HF2200	HF2250	Horizontal	Front	20	75 psi	16" x 32" x 16"	Stainless Steel	47
S1800	S1850	Vertical	Front	20	100 psi	20.25"x 20" x 27"	Marine Galvanized Steel	46
S1800W	S1850W	Vertical	Front	20	100 psi	20.25"x 20" x 27"	White Epoxy	46
	S1850EW	Vertical	Electric	20	100 psi	20.25"x 20" x 27"	White Epoxy	46
	S1850WSR	Vertical	Front	20	75 psi	20.25"x 20" x 27"	White Epoxy	46
S1900	S1950	Vertical	Front	20	100 psi	20.25"x 20" x 27"	Stainless Steel	45
S1900E		Vertical	Electric	20	100 psi	20.25"x 20" x 27"	Stainless Steel	45
	H2850ES-3000	Horizontal	Electric	28	100 psi	16" x 40" x 16"	Stainless Steel	59
	H2850ES-4500	Horizontal	Electric	28	100 psi	16" x 40" x 16"	Stainless Steel	59
	H2850EW-3000	Horizontal	Electric	28	100 psi	16" x 40" x 16"	White Epoxy	59
	H2850EW-4500	Horizontal	Electric	28	100 psi	16" x 40" x 16"	White Epoxy	59

NOTE: All models in available in The Americas only.

S300W - 1250W element and requires a 15A Circuit Breaker

3000 and 4500 models have a 3000W and 4000W element respectively and requires a 15A Dual Breaker (3000) or 20A Dual Breaker (4500)

All other models have a 1500W element and require a 15A Circuit Breaker (120V) or 10A Dual Breaker (240V)

Note: All Whale Water Heaters must be installed and serviced by a qualified electrician in accordance with the Whale appliance installation and operating instructions and appropriate electrical regulations and certifications.